


## Precision Ball Screws

## Single Nut with Flange

## Backlash type/Preload type



Unit : mm

Ball Nut Model number	Shaft nominal dia. d	Lead	Ball size	BCD	Lead angle	Root dia. d <sub>0</sub>	Number of Circuit	Basic Load Rating N		Nut Rigidity N/μm	Nut dimension										Ball Nut Model number
								Dynamic Ca	Static Coa		Nut type	D	Df	L	L <sub>1</sub>	F	W	V	Dp	Bolt Hole X	
FBS 01800.5 A	1.8	0.5	0.4	1.95	4° 40'	1.5	2.7×1	110 / -	130 / -	19 / -	1	6	14	8.5	7	1.5	8	-	10	2.4	FBS 01800.5 A
FBS 0300.5 A	3	0.5	0.4	3.10	2° 56'	2.6	2.7×1	150 / -	220 / -	29 / -	1	8	16	11	8	3	8	-	12	2.4	FBS 0300.5 A
FBS 0301 B	3	1	0.6	3.18	5° 43'	2.4	3.7×1	330 / -	440 / -	42 / -	1	9	19	14	11	3	11	-	14	2.9	FBS 0301 B
FBS 0400.5 A	4	0.5	0.4	4.10	2° 13'	3.6	2.7×1	160 / -	290 / -	36 / -	1	10	20	13	10	3	12	-	15	2.9	FBS 0400.5 A
FKB 0401 A	4	1	0.6	4.15	4° 23'	3.4	1×3	300 / 300	430 / 430	38 / 59	2	9	19	13	10	3	11	13	14	2.9	FKB 0401 A
FBS 0401 A	4	1	0.8	4.15	4° 23'	3.3	2.7×1	420 / 270	570 / 290	40 / 34	1	10	20	12	9	3	12	14	15	2.9	FBS 0401 A
FBS 0401 B	4	1	0.8	4.15	4° 23'	3.3	3.7×1	560 / 350	790 / 400	54 / 45	1	11	23	17	13	4	13	15	17	3.4	FBS 0401 B
FBS 0402 A	4	2	0.8	4.15	8° 43'	3.3	2.7×1	420 / 260	570 / 290	39 / 33	1	11	23	19	15	4	13	15	17	3.4	FBS 0402 A
FEB 0404 A	4	4	0.8	4.2	16° 51'	3.3	2.6×2	750 / -	1150 / -	73 / -	3	11	23	17.5	11	3	-	15	17	3.4	FEB 0404 A
FEB 0408 A	4	8	0.6	4.15	31° 32'	3.4	1.7×4	590 / -	1110 / -	78 / -	3	11	23	20	12	3	-	15	17	3.4	FEB 0408 A

Note 1) The diameter of one of the Screw Shaft ends must be less than the Screw Shaft Root diameter, otherwise Ball Nut cannot be installed.

Note 2) Ball Nut dimension is without seal at the both ends.

If the seals are required, Ball Nut dimension should be changed, in that case, please ask KSS.

Some type of Ball Nuts cannot equip with seals, please ask KSS representative.

Note 3) The Rigidity values shown in the table are theoretical values of Ball Nut Rigidity calculated from the amount of Elastic Displacement under the following conditions.

Backlash type ; Apply the Axial load equivalent to 30% of the Basic Dynamic Load Rating Ca.

Preload type ; Apply the Preload equivalent to 5% of the Basic Dynamic Load Rating Ca.

For Axial load or Preload condition other than the above, see the formula in p-A823, you can calculate Rigidity using this formula.

Note 4) All models are Right-hand Screw. If Left-hand Screw is required, please ask KSS representative.

Note 5) Basic Load Rating and Rigidity for Backlash type and Preload type are described in the same cell.

Basic Load Rating N		Nut Rigidity N/μm
Dynamic Ca	Static Coa	
1000 / 640	3300 / 1650	164 / 138
		Preload type
		Backlash type